

This document consists of 20 pages

# **Text Instructions**

## 1. Annotations and abbreviations

Annotation in scoris	Meaning
√and <b>x</b>	
BOD	Benefit of doubt
FT	Follow through
ISW	Ignore subsequent working
M0, M1	Method mark awarded 0, 1
A0, A1	Accuracy mark awarded 0, 1
B0, B1	Independent mark awarded 0, 1
SC	Special case
^	Omission sign
MR	Misread
Highlighting	
Other abbreviations in	Meaning
mark scheme	
E1	Mark for explaining a result or establishing a given result
dep*	Mark dependent on a previous mark, indicated by *
cao	Correct answer only
oe	Or equivalent
rot	Rounded or truncated
soi	Seen or implied
www	Without wrong working
AG	Answer given
AU	
awrt	Anything which rounds to

### 2. Subject-specific Marking Instructions for A Level Mathematics A

- Annotations should be used whenever appropriate during your marking. The A, M and B annotations must be used on your standardisation scripts for responses that are not awarded either 0 or full marks. It is vital that you annotate standardisation scripts fully to show how the marks have been awarded. For subsequent marking you must make it clear how you have arrived at the mark you have awarded.
- An element of professional judgement is required in the marking of any written paper. Remember that the mark scheme is designed to assist in marking incorrect solutions. Correct solutions leading to correct answers are awarded full marks but work must not be judged on the answer alone, and answers that are given in the question, especially, must be validly obtained; key steps in the working must always be looked at and anything unfamiliar must be investigated thoroughly. Correct but unfamiliar or unexpected methods are often signalled by a correct result following an apparently incorrect method. Such work must be carefully assessed. When a candidate adopts a method which does not correspond to the mark scheme, escalate the question to your Team Leader who will decide on a course of action with the Principal Examiner.

  If you are in any doubt whatsoever you should contact your Team Leader.
- c The following types of marks are available.

#### М

A suitable method has been selected and *applied* in a manner which shows that the method is essentially understood. Method marks are not usually lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. In some cases the nature of the errors allowed for the award of an M mark may be specified.

### Α

Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated Method mark is earned (or implied). Therefore M0 A1 cannot ever be awarded.

### В

Mark for a correct result or statement independent of Method marks.

#### E

Mark for explaining a result or establishing a given result. This usually requires more working or explanation than the establishment of an unknown result.

Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored. Sometimes this is reinforced in the mark scheme by the abbreviation isw. However, this would not apply to a case where a candidate passes through the correct answer as part of a wrong argument.

- When a part of a question has two or more 'method' steps, the M marks are in principle independent unless the scheme specifically says otherwise; and similarly where there are several B marks allocated. (The notation 'dep\*' is used to indicate that a particular mark is dependent on an earlier, asterisked, mark in the scheme.) Of course, in practice it may happen that when a candidate has once gone wrong in a part of a question, the work from there on is worthless so that no more marks can sensibly be given. On the other hand, when two or more steps are successfully run together by the candidate, the earlier marks are implied and full credit must be given.
- The abbreviation FT implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A and B marks are given for correct work only differences in notation are of course permitted. A (accuracy) marks are not given for answers obtained from incorrect working. When A or B marks are awarded for work at an intermediate stage of a solution, there may be various alternatives that are equally acceptable. In such cases, what is acceptable will be detailed in the mark scheme. If this is not the case please, escalate the question to your Team Leader who will decide on a course of action with the Principal Examiner.

  Sometimes the answer to one part of a question is used in a later part of the same question. In this case, A marks will often be 'follow through'. In such cases you must ensure that you refer back to the answer of the previous part question even if this is not shown within the image zone. You may find it easier to mark follow through questions candidate-by-candidate rather than question-by-question.
- Unless units are specifically requested, there is no penalty for wrong or missing units as long as the answer is numerically correct and expressed either in SI or in the units of the question. (e.g. lengths will be assumed to be in metres unless in a particular question all the lengths are in km, when this would be assumed to be the unspecified unit.) We are usually quite flexible about the accuracy to which the final answer is expressed; over-specification is usually only penalised where the scheme explicitly says so. When a value is given in the paper only accept an answer correct to at least as many significant figures as the given value. This rule should be applied to each case. When a value is not given in the paper accept any answer that agrees with the correct value to 2 s.f. Follow through should be used so that only one mark is lost for each distinct accuracy error, except for errors due to premature approximation which should be penalised only once in the examination. There is no penalty for using a wrong value for g. E marks will be lost except when results agree to the accuracy required in the question.
- g Rules for replaced work: if a candidate attempts a question more than once, and indicates which attempt he/she wishes to be marked, then examiners should do as the candidate requests; if there are two or more attempts at a question which have not been crossed out, examiners should mark what appears to be the last (complete) attempt and ignore the others. NB Follow these maths-specific instructions rather than those in the assessor handbook.
- h For a genuine misreading (of numbers or symbols) which is such that the object and the difficulty of the question remain unaltered, mark according to the scheme but following through from the candidate's data. A penalty is then applied; 1 mark is generally appropriate, though this may differ for some units. This is achieved by withholding one A mark in the question. Marks designated as cao may be awarded as long as there are no other errors. E marks are lost unless, by chance, the given results are established by equivalent working. 'Fresh starts' will not affect an earlier decision about a misread. Note that a miscopy of the candidate's own working is not a misread but an accuracy error.
- If a calculator is used, some answers may be obtained with little or no working visible. Allow full marks for correct answers (provided, of course, that there is nothing in the wording of the question specifying that analytical methods are required). Where an answer is wrong but there is some evidence of method, allow appropriate method marks. Wrong answers with no supporting method score zero. If in doubt, consult your Team Leader.
- if in any case the scheme operates with considerable unfairness consult your Team Leader.

	Questio	on	Answer	Marks	AO	Guidan	ce
1	(a)		5	<b>B</b> 1	1.1		
			Substituting $x = -3$ into $ 2x - 1 $	M1	1.1a		
			7	<b>A1</b>	1.1		
				[3]			
1	<b>(b)</b>		2x-1>x+1 therefore $x>2$	<b>B</b> 1	1.1	OR	OR
						<b>B1</b> for a sketch of $y =  2x - 1 $ and	<b>B1</b> $(2x-1)^2 > (x+1)^2$ seen
						y = x + 1 on the same axes	
			-(2x-1) > x+1 (Allow ± in bracket)	M1	3.1a	M1 attempt to find the points of intersection	M1 attempt to multiply out and simplify, then solve
							quadratic
			<i>x</i> < 0	A1	1.1	A1 obtain $x > 2$ and $x < 0$	A1 obtain $x > 2$ and $x < 0$
			$\{x:x<0\}\cup\{x:x>2\}$	A1	2.5	<b>A1</b> $\{x: x < 0\} \cup \{x: x > 2\}$	<b>A1</b> $\{x: x < 0\} \cup \{x: x > 2\}$
				[4]			
2	(a)		$\frac{0.25}{2} \left(1 + 0.7071 + 2 \left(0.970 + 0.8944 + 0.8\right)\right)$	B1	1.1	Obtain all five ordinates and no others:	Accept exact values: $1, \frac{4}{\sqrt{17}}$ ,
						0.7071, 0.8944, 1, 0.8, 0.970	$\frac{2}{\sqrt{5}}, \frac{4}{5}, \frac{1}{\sqrt{2}}$
				M1	1.1a	Use correct structure for trapezium rule with $h = 0.25$	x-coordinates used <b>M0</b> . Omission of large brackets unless implied by correct answer <b>M0</b>
			0.880	A1 [3]	1.1	0.880 or better (0.87953077)	Accept 0.88 (0.87953077)
2	(b)		"Use smaller intervals" or " use more trapezia"	B1 [1]	2.4		

Question	Answer	Marks	AO	Guidan	ce
3	$DR$ $5\sin 2x = 3\cos x \implies 10\sin x \cos x = 3\cos x$	B1	1.1	Use $\sin 2x = 2\sin x \cos x$ to obtain correct identity	SC2 For use of identity followed by cancelling $\cos x$ , leading to $\sin x = \frac{3}{10}$ .
	$\cos x (10\sin x - 3) = 0$	M1	1.1a	Attempt to factorise	
	$\cos x \neq 0 \text{ for } 0^{\circ} < x < 90^{\circ}$	E1	2.1		
	so $\sin x = \frac{3}{10}$	<b>A1</b>	1.1		
		[4]			
4	When $\theta$ is small $1 + \cos \theta - 3\cos^2 \theta$ $\approx 1 + \left(1 - \frac{1}{2}\theta^2\right) - 3\left(1 - \frac{1}{2}\theta^2\right)^2$	M1	1.1a	Attempt to use $\cos \theta \approx 1 - \frac{1}{2}\theta^2$ or $= 1 + \left(1 - \frac{1}{2}\theta^2 +\right)$	OR M1 Attempt to use $\cos \theta \approx 1 - \frac{1}{2}\theta^2$
	$=1+\left(1-\frac{1}{2}\theta^{2}\right)-3\left(1-\theta^{2}+\frac{1}{4}\theta^{4}\right)$ $=1+1-\frac{1}{2}\theta^{2}-3+3\theta^{2}-\frac{3}{4}\theta^{4}$	M1	1.1	$-3\left(1-\frac{1}{2}\theta^2+\ldots\right)^2$ Multiply out	M1 use trigonometric identity $1 + \cos \theta - 3\cos^2 \theta$ $= 1 + \cos \theta - \frac{3}{2} - \frac{3}{2}\cos 2\theta$
	Since $\theta$ is small, we can neglect the higher order terms	E1	2.5	For explanation of loss of $\theta^4$ term and consistent use of notation throughout (Working need not be fully correct)	E1 For showing clearly which identity has been used and consistent use of notation throughout
	so $1 + \cos \theta - 3\cos^2 \theta \approx -1 + \frac{5}{2}\theta^2$ as required	E1	2.1	AG Clearly obtained www Condone $\theta^4$ term missing without explanation and inconsistent notation	E1 AG Clearly obtained www Condone inconsistent notation
		[4]			

	Questio	n	Answer	Marks	AO	Guidanc	ee
5	(a)		Obtain $1 + \frac{1}{3} px$	B1	1.1		
			$\left(\frac{1}{2}\right)\left(\frac{1}{3}\right)\left(\frac{-2}{3}\right)\left(px\right)^2$	M1	1.1		Attempt the $x^2$ term at least
							in the form ${}^6C_2kx^2$
			Obtain $1 + \frac{1}{3} px - \frac{1}{9} p^2 x^2$	A1	1.1	Must be simplified	
				[3]			
5	(b)		$(1+qx)(1+\frac{1}{3}px-\frac{1}{9}p^2x^2)$	M1	3.1a		Expand $(1+qx)$ and their
			$=1+\left(\frac{1}{3}p+q\right)x+\left(\frac{1}{3}pq-\frac{1}{9}p^{2}\right)x^{2}$				$1 + \frac{1}{3}px - \frac{1}{9}p^2x^2$ and
			(3F - 1) - (3F1 - 9F )				compare coefficients
			$\frac{1}{3}p + q = 1$ (*)	M1	3.1a	Obtain two equations in $p$ and $q$ and	
			$\frac{1}{3}pq - \frac{1}{9}p^2 = -\frac{2}{9}$			show evidence of substitution for $p$ or $q$ to obtain an equation in one	
						variable	
			$2p^2 - 3p - 2 = 0$	M1	1.1	Solve a 3 term quadratic equation in	Or $18q^2 - 27q + 7 = 0$
						a single variable.	Solve their quadratic
			$p = 2 \text{ or } -\frac{1}{2}$	<b>A1</b>	1.1	Obtain any two values	
			$q=\frac{1}{3}$ or $\frac{7}{6}$	A1FT	1.1	Obtain all 4 values, or FT their <i>p</i> and	with indication of correct
			- 3			(*)	pairings
				[5]			

Question	Answer	Marks	AO	Guidano	ee
6	$\frac{dy}{dx} = 2x + k + 4x^{-2}$ $2(-2) + k + 4(-2)^{-2} = 0$	M1	1.1a	Attempt to differentiate	Power decreases by 1 for at least 2 terms
	$2(-2)+k+4(-2)^{-2}=0$	M1	3.1a	Substitute $x = -2$ , equate to 0 and attempt to solve	
	k=3	A1	1.1	1	
	$\frac{\mathrm{d}^2 y}{\mathrm{d}x^2} = 2 - 8x^{-3}$				
	$2 - 8x^{-3} = 0$	M1	3.1a	Equate second derivative to 0 and attempt to solve	
	$x = 4^{\frac{1}{3}}$	<b>A1</b>	1.1		
	for $x < 4^{\frac{1}{3}} \Rightarrow \frac{d^2 y}{dx^2} < 0$ for $x > 4^{\frac{1}{3}} \Rightarrow \frac{d^2 y}{dx^2} > 0$	E1	2.1	Consider convex/concave either side of $x = 4^{\frac{1}{3}}$ and conclude	
	$for x > 4^{\frac{1}{3}} \Rightarrow \frac{d^2 y}{dx^2} > 0$				
	When $x = 4^{\frac{1}{3}}$ , $\frac{dy}{dx} \neq 0$ hence not a stationary point	E1	2.1	Consider gradient at $x = 4^{\frac{1}{3}}$ , or justify that $x = -2$ is the only stationary point	
		[7]			

	Question	Answer	Marks	AO	Guidan	ce
7	(a)	$u = x^2 + 1$	M1	1.1a	Attempt a substitution of $x$ and $dx$	$\mathbf{M0} \text{ for } du = dx$
		$du = 2xdx$ $\frac{5}{2} \int (u-1)u^{\frac{1}{2}} du$	M1	1.1	Replace as far as $k \int (u-1)u^{\frac{1}{2}}du$	
		$\frac{5}{2}\int \left(u^{\frac{3}{2}}-u^{\frac{1}{2}}\right)\mathrm{d}u$	<b>A1</b>	1.1		
		$u^{\frac{5}{2}} - \frac{5}{3}u^{\frac{3}{2}} + c$	M1	1.1	Integrate their integral if in $u$	
		$(x^2+1)^{\frac{5}{2}} - \frac{5}{3}(x^2+1)^{\frac{3}{2}} + c$	A1	1.1	Do not condone missing $+c$ in both (a) and (b)	
			[5]			
7	(b)	$\int \tan^2 \theta  d\theta = \int \left( \sec^2 \theta - 1 \right) d\theta$	M1	1.1	Award for sight of the intermediate result	OR M1 $\int \theta \tan^2 \theta  d\theta = \int \theta \left( \sec^2 \theta - 1 \right) d\theta$
		$= \tan \theta - \theta$	A1	1.1		$\begin{vmatrix} \mathbf{A}1 \\ = \int \theta \sec^2 \theta  d\theta - \int \theta  d\theta \end{vmatrix}$
		$u = \theta, dv = \tan^2 \theta$	M1	3.1a	Recognise integration by parts with appropriate choice of $u$ and $dv$	$\mathbf{M1}  u = \theta, \ dv = \sec^2 \theta$
		$So \int \theta \tan^2 \theta d\theta = \theta (\tan \theta - \theta) - \int (\tan \theta - \theta) d\theta$	A1	1.1	Obtain correct intermediate result	<b>A1</b> So $\int \theta \tan^2 \theta d\theta$
		$-\frac{1}{2}\theta^2 + \theta \tan \theta - \ln \left  \sec \theta \right  + c$	A1	1.1		$= \theta \tan \theta - \int \tan \theta  d\theta - \frac{1}{2} \theta^{2}$ $A1$ $= -\frac{1}{2} \theta^{2} + \theta \tan \theta - \ln  \sec \theta  + \alpha$
			[5]			

	Questic	on	Answer	Marks	AO	Guidan	ice
8	(a)		DR $BE = \sqrt{3} \text{ from the standard triangle } BDE$ $BC = AB\cos 45$ $BC = \frac{1+\sqrt{3}}{\sqrt{2}} = \frac{\sqrt{2}+\sqrt{6}}{2}$	B1 M1 E1	2.2a 2.1 2.2a	Or $AB = 1 + \sqrt{3}$ seen oe or Pythagoras' theorem AG	B0 for decimal  Must be seen $\frac{1+\sqrt{3}}{\sqrt{2}}$ must be seen
			V2 2	[3]			$\sqrt{2}$ must be seen
8	(b)		Triangle ABC is isosceles so BC = AC but $AC = CD + \sqrt{2}$ so $CD = \frac{\sqrt{2} + \sqrt{6}}{2} - \sqrt{2}$ $= \frac{\sqrt{6} - \sqrt{2}}{2}$	B1 M1	2.4	State or imply that $BC = AC$ and state $AC = CD + \sqrt{2}$ Obtain expression for $CD$ , may be unsimplified	M0 if decimals seen
			$\sin 15 = \frac{CD}{BD} = \frac{\sqrt{6} - \sqrt{2}}{2} \div 2 = \frac{\sqrt{6} - \sqrt{2}}{4}$	A1 [3]	2.2a	Obtain expression for sin15 and simplify to answer given	SC1 for showing using addition formula
9	(a)		Attempt resolution of forces  Horizontal component = $5 + 2\cos 40$ (= 6.5321)  Vertical component = $2\sin 40$ (= 1.2856) $\sqrt{6.5321^2 + 1.2856^2} = 6.66 \text{ N}$	M1 A1	1.1a 1.1 1.1	Allow sin/cos confusion  Allow for either the horizontal or vertical component correct  Use correct method for magnitude	OR M1 Form triangle of forces A1 Use cosine rule with 140° A1 Obtain 6.66 N
9	(b)		$\tan^{-1}\left(\frac{2\sin 40}{5 + 2\cos 40}\right) = 11.1^{\circ}$	[3] B1FT	1.1	FT their components from part (i)	
				[1]			

	Questio	n Answer	Marks	AO	Guidano	ee
10	(a)	$R$ $100 \mathrm{N} + \mathrm{Friction}$ $20 \mathrm{g} \mathrm{N}$	B1	2.1	Any equivalent which makes clear the relationships between:  Reaction, 100 N force, friction acting upwards, weight of 20 g N  A diagram is not <i>necessary</i> provided that sufficient explanation is given.	Contact force 100 N 20g
		Resolve parallel to the slope: $100 + F - 20g \sin \alpha = 0$ (*)	M1	3.3		
		Resolve perpendicular to the slope and friction force is maximum: $R = 20g \cos \alpha$ and $F = \mu R$	M1	3.3		
		Substitute and obtain $20g \sin \alpha = 20g \mu \cos \alpha + 100$	E1	1.1	AG	
10	(b)	All forces shown on diagram of inclined plane	[4]		Reaction, 150 N force, friction acting	
		Resolve parallel to the slope: $150 - F - 20g \sin \alpha = 0$ (**)	B1	3.3	downwards, weight of 20 g N	
		From * and ** $250 - 40g \sin \alpha = 0$	M1	3.4	Eliminate $\mu$ and attempt to solve for $\alpha$ .	One valid step after elimination required
		$\alpha = \sin^{-1} \frac{25}{4g}$	A1	1.1		
			[3]			

	Questio	n	Answer	Marks	AO	Guidano	ee
11	(a)		$\mathbf{v} = 6t^2\mathbf{i} + (10t - 4)\mathbf{j}$	B1	1.1	At least one term reduces in power	
			$\mathbf{v} = 2.94\mathbf{i} + 3\mathbf{j}$ $90 - \tan^{-1} \left(\frac{2.94}{3}\right)$	M1	3.1a	by 1 Substitution of $t = 0.7$ , use $\tan^{-1}\left(\frac{y}{x}\right)$ and obtain $90 - 45.578 = 44.4^{\circ}$ to give a 3 figure bearing	For a complete method to find a bearing
			=044°	<b>A1</b>	1.1		
				[3]			
11	(b)		$\mathbf{a} = 12t\mathbf{i} + 10\mathbf{j}$	M1	1.1	Attempt differentiation of v	
			$\mathbf{a} = 8.4\mathbf{i} + 10\mathbf{j}$	<b>A1</b>	1.1	Substitute $t = 0.7$	
			Use $\mathbf{F} = m\mathbf{a}$ and use Pythagoras	M1	3.3		
			Obtain 1.57 N	A1FT	3.4	FT their <b>a</b> at $t = 0.7$	
				[4]			
11	(c)		$6t^2 = 10t - 4$ $6t^2 - 10t + 4 = 0$ so $t = 1$ or $\frac{2}{3}$ E.g. <b>i</b> component always positive so both values are valid	M1 E1	2.2a 2.3	Equate i and j components and solve FT their v from part (i) if it leads to a quadratic BC Must include comment on why equating components is sufficient in this case.	
				[2]			

	Questi	on	Answer	Marks	AO	Guidance		
12	(a)	(i)	Vertical component of $U = 10\sin 40$	B1	1.1			
			Vertical component of velocity = $10\sin 40 - gt =$	M1	3.3	Use $v = u - gt$ with $v = 0$		
			0			Allow sign error or sin/cos confusion		
			Obtain $t = 0.656$	<b>A1</b>	1.1		0.6559057242	
			Vertical displacement = $10 \sin 40t - \frac{1}{2}gt^2(+c)$	M1	3.4	Use $s = ut + \frac{1}{2}gt^2$ or $s = \int v dt$	Allow if initial height not seen	
							M1 may be awarded if seen in part (a)(ii)	
			Obtain $2.11 + 1.5 = 3.61 \mathrm{m}$	A1FT	1.1	FT their "2.11" + 1.5	3.608040363	
				[5]				
12	(a)	(ii)	Horizontal component of $U = 10\cos 40$	B1	1.1	Use the horizontal component of $U$	Allow 10sin 40 if	
							10cos 40 given in part (i)	
			$6=10\cos 40t$	M1	3.3	Attempt horizontal resolution		
						equated to 6		
			0.702			Allow sin/cos error	0.7000440706	
			t = 0.783	A1	1.1		0.7832443736	
			$(2.028586218+1.5)-2.5=1.03 \mathrm{m}$	A1	3.4	Substitute <i>t</i> in		
						$10\sin 40t - \frac{1}{2}gt^2$ (+1.5) and subtract		
						2.5		
				[4]				
12	(b)		Use $1 = 6 \tan 40 - \frac{(9.8)6^2 \sec^2 40}{2U^2}$	M1	3.1b	Use $y = x \tan \theta - \frac{gx^2 \sec^2 \theta}{2U^2}$ with	Allow $y = 2.5$ for <b>M1</b>	
						$x=6$ and $\theta=40$		
			$U^2 = 74.5$	M1	1.1	Attempt to make $U$ the subject	OR BC	
			Obtain $U=8.63$	<b>A1</b>	1.1	BC	8.631677404	
				[3]				

E.g. Not very appropriate since it relies on throwing at a very precise angle and velocity. E.g. Not very appropriate since it does not take into account air resistance which will cause the ball to fall short E.g. Not very appropriate since the target she is aiming at is actually a ring, so she has some flexibility  [1]  12 (d) E.g. The ball could not be modelled as a particle so that air resistance is included. E.g. The angle could be a variable. E.g. Angles and velocities could be given as ranges.		Question	Answer	Marks	AO	Guidance	
12 (d) E.g. The ball could not be modelled as a particle so that air resistance is included. E.g. The angle could be a variable. E.g. Angles and velocities could be given as	12	(c)	throwing at a very precise angle and velocity.  E.g. Not very appropriate since it does not take into account air resistance which will cause the ball to fall short  E.g. Not very appropriate since the target she is aiming at is actually a ring, so she has some	E1	3.5a	E1 for one valid statement	
so that air resistance is included.  E.g. The angle could be a variable.  E.g. Angles and velocities could be given as				[1]			
E.g. The hoop could be modelled as a line of points.	12	(d)	so that air resistance is included. E.g. The angle could be a variable. E.g. Angles and velocities could be given as ranges. E.g. The hoop could be modelled as a line of	E1	3.5c	E1 for one valid improvement	

Question		n	Answer	Marks	AO	Guidance	
13 (a)			Resolving vertically to the plane for Particle A	B1	1.1	Obtain $\frac{4}{5}mg$	
			$R = mg\cos\alpha = \frac{4}{5}mg$				
			Since A is in motion, $F_s = \mu R = \frac{1}{3} \left(\frac{4}{5}\right) mg = \frac{4}{15} mg$	B1	2.2a	Obtain $\frac{4}{15}mg$	
			Resolving horizontally to the plane for both particles:	M1	3.1b	Must obtain two equations in T and a	
			particles			Particle A:	
						Attempt resolution as far as stating	
			$_{T}$ 13mg			$T - F_s - mg \sin \alpha = ma$	
			$1 - \frac{1}{15} = ma$			Particle B:	
			$T - \frac{13mg}{15} = ma$ $-T + \frac{16mg}{5} = 4ma$	A1	2.1	Attempt resolution as far as stating $-T + 4mg \sin \beta = 4ma$	
			3	M1	1.1	Solve their simultaneous equations to	
				1411	1.1	find $a$ in terms of $g$ .	
			$a = \frac{7g}{15}$	E1	2.4	AG Solution must include clear diagrams or explanation for $F_s$ and for horizontal resolutions.	
				[6]			
13	(b)		$\frac{7g}{30} = 2 \times \frac{7g}{15} \times s$	M1	1.1	Use $v^2 = 0^2 + 2as$	
			$S = \frac{1}{4}$	<b>E1</b>	2.1	AG Must include sufficient working	
			4			to justify the given answer from the constant acceleration formula	
				[2]			

Question Answer		Marks	AO	Guidance	
14	Let $F_G$ be the frictional force at ground level and	B1	2.1	Either on a diagram or in words, B1	
	$R_{\rm G}$ the reaction			is awarded for a clear definition of	
	Let $F_{W}$ be the frictional force at the wall and $R_{W}$			the force variables used	
	the reaction				
	Let <i>x</i> be the distance the man can ascend before				
	the ladder slips				
	$F_G = \frac{1}{2}R_G$ and $F_W = \frac{1}{3}R_W$	B1	3.3	Both statements required	
	Resolve horizontally and vertically:	B1	3.1b	Both resolutions required	
	$F_G = R_W$			Accept numerical value of g used	
	$R_G + F_W = 105g$				
		M1	1.1	Attempt to solve the 4 equations	
				simultaneously to obtain at least two	
				numerical values for the variables.  May be implied by later working	
	$F_W = 15g$	B1	3.2a	<b>B1</b> for either $F_W$ and $R_W$ or $F_G$ and $R_G$	
		Di	3.2a	bi for either r w and r w or r G and r G	
	$R_W = 45g = F_G$				
	$R_G = 90g$				
	Moments about the foot of the ladder:	M1	3.3	Allow sign errors and sin/cos	Or similarly about the top of
	$35g(3.5\cos 45) + (70g\cos 45)x = 45g(7\cos 45)$			confusion	the ladder
	$+15g(7\sin 45)$	<b>A1</b>	3.4	Correct statement	
	x = 4.25	<b>A1</b>	1.1	cao	
		[8]			